




## Model


☐ D320 ☐ D400 ☐ D420 ☐ D570 ☐ D970

## D Bins

.75" (1.90 cm) Bin drain



D320  
264 lbs. (120 kgs)



D400  
365 lbs. (166 kgs)



D420  
383 lbs. (174 kgs)



D570  
532 lbs. (241 kgs)



D970  
882 lbs (400 kgs)



Ergonomic NSF approved  
sanitary ice scoop included

## D Bin Features

**New Sanitary Scoop** Ergonomic NSF approved sanitary ice scoop included with each bin. Built-in knuckle and thumb guard. Unique molded retaining lip allows maximum scooping every time. Per scoop capacity approximately 5.3/ lbs (2.4 kg)

**Scoop Holder options** New built-in scoop holder, keeps the ice scoop handle above the ice, or purchases the optional NSF approved External Scoop Holder Kit # K00461.

**New Door design** Clever built in side grips allow you to lift the bin door from anywhere you are standing (left, right or center) even when you have just one hand free.

### Foamed Insulated Door

Insulates the ice bin, reduces sweat on the door, helps keep ice lasting longer.

**Stay up door** Unique cammed bin door self-latch keeps the door in the open position and keeps the employee safe when scooping ice.

**Ergonomic Door design** Door is angled 53 degrees to allow for easier access to the ice in the bin especially when scooping from the bottom.

**Duratech Metal Finish** Manitowoc exterior material has better corrosion resistance than stainless steel, is smudge resistant and easy to keep clean.

**New Bin liner** Polyurethane Artic Blue bin liner accentuates the crisp clear ice from a Manitowoc Ice Machine.

## Warranty

Bin & Accessories: 3 Year Parts & Labor.

| D Bin Model | D-Bin Capacities      |        |                      |       | D-Bin Dimensions |      |       |       |       |      |
|-------------|-----------------------|--------|----------------------|-------|------------------|------|-------|-------|-------|------|
|             | *Application Capacity |        | **2018 AHRI Capacity |       | Height           |      | Width |       | Depth |      |
|             | lbs.                  | kgs    | Cu. ft               | Cu. M | in.              | cm   | in.   | cm    | in.   | cm   |
| D320        | 264                   | 119.90 | 8.9                  | 0.25  | 38               | 96.5 | 22    | 55.9  | 34    | 86.4 |
| D420        | 383                   | 173.79 | 12.9                 | 0.37  | 50               | 127  | 22    | 55.9  | 34    | 86.4 |
| D400        | 365                   | 165.70 | 12.3                 | 0.35  | 38               | 96.5 | 30    | 76.2  | 34    | 86.4 |
| D570        | 532                   | 241.14 | 17.9                 | 0.51  | 50               | 127  | 30    | 76.2  | 34    | 86.4 |
| D970        | 882                   | 400.11 | 29.7                 | 0.84  | 50               | 127  | 48    | 121.9 | 34    | 86.4 |

\*Application Capacity based on 90% of the total volume x 33 lbs/ ft<sup>3</sup> average density of ice. Ice must be managed

\*\*\*2018 AHRI certified measurement for bin capacity

Above bin heights include leg height of 6" / 15.24 cm  
All bins include a sanitary plastic scoop and one set of adjustable legs chrome legs (6-7.75in/15.24-20.32cm).  
External Scoop holder order separately Kit # K00461  
Metal Scoop order separately Kit # K00463



Manitowoc Ice reserves the right to make changes to the design or specifications without prior notice.



## D Bins

| Indigo Ice Machines Series   |         |       |        |        |        |        |                    |                                |                                |                    |                       |                   |
|------------------------------|---------|-------|--------|--------|--------|--------|--------------------|--------------------------------|--------------------------------|--------------------|-----------------------|-------------------|
| Machine                      |         |       | iT420  | iT620  | iT0300 | iT450  | iT0500<br>&iF0500N | iF0600N,<br>iF0600C,<br>iT0750 | iF0900N,<br>iT0900,<br>iF0900C | iT1200,<br>iT1200C | iF1400C,<br>iF1800C   | iT1500,<br>iT1900 |
| Machine Capacity<br>@90/70 F |         |       | 375    | 465    | 240    | 378    | 440                | 555, 530                       | 710, 714                       | 950, 1000          | 1200<br>1470<br>1600  | 1360<br>1455      |
| Bins                         | Bin Cap | Width | 22"    | 22"    | 30"    | 30"    | 30"                | 30"                            | 30"                            | 30"                | 30"                   | 48"               |
| D320                         | 264     | 22"   | *      | *      |        |        |                    |                                |                                |                    |                       |                   |
| D420                         | 383     | 22"   | *      | *      |        |        |                    |                                |                                |                    |                       |                   |
| D400                         | 365     | 30"   | K00472 | K00472 | *      | *      | *                  | *                              | NR                             | NR                 | NR                    |                   |
| D570                         | 532     | 30"   | K00472 | K00472 | *      | *      | *                  | *                              | *                              | *                  | NR                    |                   |
| D970                         | 882     | 48"   | NR     | NR     | NR     | K00470 | K00470             | K00470                         | K00470                         | K00470             | K00471<br>+<br>K00470 | *                 |

| Manitowoc Flaker and Nugget Machines |         |         |         |         |         |         |                      |                      |         |                       |          |
|--------------------------------------|---------|---------|---------|---------|---------|---------|----------------------|----------------------|---------|-----------------------|----------|
|                                      |         | Machine | RNP0320 | RFP0320 | RNP0620 | RFP0620 | RNF1020              | RFF1220C             | RNF1100 | RFF1300 &<br>RNF2000C | RFF2200C |
| Machine cap                          |         |         | 251     | 286     | 451     | 540     | 825                  | 958                  | 825     | 874                   | 1702     |
| Bins                                 | Bin cap | Width   | 22"     | 22"     | 22"     | 22"     | 22"                  | 22"                  | 30"     | 30"                   | 36.7"    |
| D320                                 | 264     | 22"     | *       | *       | NR      | NR      | NR                   | NR                   |         |                       |          |
| D420                                 | 383     | 22"     | *       | *       | *       | *       | NR                   | NR                   |         |                       |          |
| D400                                 | 365     | 30"     | K00472  | K00472  | K00472  | K00472  | NR                   | NR                   | NR      | NR                    |          |
| D570                                 | 532     | 30"     | NR      | K00472  | K00472  | K00472  | NR                   | NR                   | *       | *                     |          |
| D970                                 | 882     | 48"     | NR      | NR      | K00473  | K00473  | K00473 if<br>2 used. | K00473 if<br>2 used. | K00470  | K00470                | K00470   |

An optional adapter is required when putting a narrower ice machine on a wider bin.

\* No adapter is needed

NR= Not Recommend. Bin too small or too large for application.

Putting a wider machine on narrower bin is not an option.

Machines side by side must be water cooled, remote, or use a top air discharge for self-contained air cooled.

Application Bin Capacity shown in lbs using the AHRI rating based on 90% of total volume x 33 lbs/ft<sup>3</sup> average density of ice.

Machine capacity shown in lbs/24hrs using the AHRI rating base at 90F ambient, 70F water temperature

## Ice Storage Bins

### Available Accessories

See price book for replacement: scoops, legs, specialty legs and casters

#### K00146 Convenient Ice Bagger

Includes bagger, D-bin adapter, and 250 bags and ties (Not for D320 or D400) Order K00068 replacement bags



#### K00461 External Scoop Holder

NSF approved. Can be mounted on the left or right side of bins, horizontally or vertically or on a wall.



#### K00463 Metal Scoop

Indestructible NFS approved aluminum alloy with sanitary knuckle and thumb guard. Works with K00461 external scoop holder or hangs inside the D-Bin series. Limited life time guarantee.



#### K00462 Secure Fastening Kit

Securely fast the Indigo NXT ice machine head to the pre-drilled inserts on the back of the D-bin series. Stainless steel flanged feet attach to bin and can be screwed to the floor



Manitowoc Ice reserves the right to make changes to the design or specifications without prior notice.