REFRIGERATOR MANUFACTURER
Turbo air
more durable, efficient, beautiful

4184 E. Conant St.
Long Beach, CA 90808
Tel. 310-900-1000
Fax. 310-900-1077
www.turboairinc.com

Project:	
Model #:	
Item #:	
Available W/H:	Qty:
Approval:	
AIA #:	SIS #:
CSI Section 11400	

Solid Door Refrigerator

Reach-In Bottom Mount
Super Deluxe Series

Model : TSR-23SD-N6
TSR-23SD-N6-L



FEATURES & BENEFITS

Self-Cleaning Condenser
The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system
- Keeps food products safe by maintaining constant temperatures
- Alarms that sound when doors are not sealed shut; protect against food spoilage that originates from cold air leaks
- Early warning alarm program detects issues before malfunction occurs
- Digital display allows for easy monitoring
- Programs interpret the condition of refrigeration systems by self-diagnosis
- Rapid cool-down function (Turbo cooling)
- Automatic evaporator fan motor delays

Hydrocarbon refrigerants (R-600a)
With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel cabinet construction
The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel top, bottom and back). It guarantees the utmost in cleanliness and long product life. Sharp corners and edges have been rounded to reduce the risk of injury. The Super Deluxe adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving
Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

Door pressure release device
Pressure relief doors are designed to eliminate vacuum pressure and allow easy door opening.

High-density polyurethane insulation
The entire cabinet structure and solid doors are foamed-in-place using high density, HCFC free polyurethane insulation.


LED interior lighting

Bottom mount compressor

- ***TSR-23SD-N6: Right hinged***
- ***TSR-23SD-N6-L: Left hinged***

Refrigerator holds 33°F ~ 38°F for the best in food preservation

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

NATURAL Refrigerant · SPEC ISO 9001:2008 · Intertek · Intertek · 5 YEAR WARRANTY · Compressor 7 YEAR WARRANTY (U.S.A. only) · ENERGY STAR® Qualified

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D x H* (inches)
TSR-23SD-N6(-L)	**1**	**19.30**	**3**	**1/8**	**1.5**	**274**	**27 x 30 3/8 x 78 1/4**

* Height does not include 5" caster height.

Solid Door Refrigerator

Reach-In Bottom Mount
Super Deluxe Series


Model : TSR-23SD-N6(-L)

ELECTRICAL DATA	
Voltage	115/60/1
Plug Type	NEMA 5-15P
Full Load Amperes	1.5
Compressor HP	1/8
Cord Length (ft.)	7
Refrigerant	R-600a
DIMENSIONAL DATA	
# of Doors	1
# of Racks Accepted	1
Net Capacity (cu. ft.)	19.30
Ext. Length Overall (in.)	27 (685mm)
Ext. Depth Overall (in.)	30 3/8 (770mm)
Ext. Height Overall (in.)*	78 1/4 (1987mm)
Int. Length Overall (in.)	23 (585mm)
Int. Depth Overall (in.)	26 1/4 (665mm)
Int. Height Overall (in.)	60 (1525mm)
# of Shelves	3
Shelf Size (L x D) (in.)	22 x 23 1/2
Net Weight (lbs.)	261
Gross Weight (lbs.)	274


Design and specifications subject to change without notice.
Actual shipping weight may differ due to extra packing materials for product protection.
* Height does not include 5" caster height.

PLAN VIEW


(unit : inch)



FRONT VIEW



TOP VIEW



SIDE VIEW

WARRANTY : 5 Year Parts and Labor Warranty
7 Year Compressor Warranty

STANDARD FEATURES

- ***Anti-corrosion coated evaporator***
- ***Door locks***
- ***Positive seal self-closing doors***
- ***Easy replaceable one piece magnetic door gaskets***
- ***Self-contained system***
- ***Solid and sturdy grille design***
- ***4" dia. swivel casters with locks on the front set***

OPTIONAL ACCESSORIES

- 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: 30278Q0100
- Half door bun tray rack: TSP-2224 (each holds up to six 18"L x 26"D sheet pans)
- Full door bun tray rack: TSP-2250-T (each holds up to fifteen 18"L x 26"D sheet pans)

Ver.20260202

NATURAL Refrigerant · ENERGY STAR® Qualified

■ Turbo Air: 800-627-0032 ■ Bake Tech Innovation: 800-500-3519
■ Warranty: 800-381-7770 ■ AC: 888-900-1002

Turbo air · BTI BAKE TECH INNOVATION · Turbo air · texaking

Continued product development may necessitate specification changes without notice.