REFRIGERATOR MANUFACTURER
Turbo air
more durable, efficient, beautiful

4184 E. Conant St.
Long Beach, CA 90808
Tel. 310-900-1000
Fax. 310-900-1077
www.turboairinc.com

| | |
|---|---|
| Project: | |
| Model #: | |
| Item #: | |
| Available W/H: | Qty: |
| Approval: | |
| AIA #: | SIS #: |
| CSI Section 11400 | |

# Chef Base Refrigerator - Flat Top

*Chef Bases*
*PRO Series*

**Patented Self-Cleaning Condenser**



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

## Model : PRCBE-36R-N-FT



## FEATURES & BENEFITS

- ***Self-Cleaning Condenser***
  The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.
- ***Hydrocarbon refrigerants (R-290)***
  With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).
- ***Digital temperature display on front panel***
- ***Strong body and durable construction***
  Built with heavy duty **16 ga**. stainless steel, Chef Base top is manufactured of one-piece reinforced stainless steel to ensure durability.
- ***Countertops***
  PRCBE-36/48/60R-N-FT supports up to 788 pounds of equipment.
  PRCBE-72/84/96R-N-FT supports up to 1,192 pounds of equipment.
- ***Each drawer accommodates up to 6" deep one (1) full size and three (3) 1/6 size pans***
- ***Top is insulated to eliminate heat transfer to the interior of cabinet***
- ***Side mount compressor unit***
  Compressors positioned on the side of the units makes servicing our units easy. Our front air intake feature also allows this model to be highly efficient in narrow spaces.
- ***High-density polyurethane insulation***
  The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- ***Durable stainless steel drawers***
- ***Stainless steel flat top***
- ***Hot gas condensate system***
- ***Full length drawer with gasket guard***
- ***Drawer slider load capacity up to 180 lbs***
- ***Magnetic snap-in gasket***
- ***Refrigerator holds 33°F ~ 38°F for the best in food preservation***
- ***4" Deep pans included***

NATURAL Refrigerant · Intertek · Intertek · 5 YEAR WARRANTY · Compressor 7 YEAR WARRANTY (U.S.A only)

| Model | Drawers | CU./FT. | HP | AMPS | Crated Weight (lbs.) | L x D* x H† (inches) |
|---|---|---|---|---|---|---|
| **PRCBE-36R-N-FT** | **2** | **4.6** | **1/4** | **3.0** | **306** | **36 1/8 x 33 1/2 x 21 3/8** |



* Depth does not include 1/2" for drawer handles. † Height does not include 4-1/2" for caster height.

# Chef Base Refrigerator - Flat Top

*Chef Bases*
*PRO Series*


## Model : PRCBE-36R-N-FT

| ELECTRICAL DATA | | |
|---|---|---|
| Voltage | | 115/60/1 |
| Plug Type | | NEMA 5-15P |
| Full Load Amperes | | 3.0 |
| Compressor HP | | 1/4 |
| Cord Length (ft.) | | 9 |
| Refrigerant | | R-290 |
| **DIMENSIONAL DATA** | | |
| Ext. Length Overall (in.) | | 36 1/8 (917mm) |
| Ext. Depth Overall (in.)* | | 33 1/2 (852mm) |
| Ext. Height Overall (in.)† | | 21 3/8 (544mm) |
| # of Drawers | | 2 |
| # of Pans | Top | (1) 1/3 size, (7) 1/6 size |
| | Bottom | (9) 1/6 size |
| Net Capacity (cu. ft.) | | 4.6 |
| Net Weight (lbs.) | | 248 |
| Gross Weight (lbs.) | | 306 |


Design and specifications subject to change without notice.
Actual shipping weight may differ due to extra packing materials for product protection.
* Depth does not include 1/2" for drawer handles. † Height does not include 4-1/2" for caster height.

## PLAN VIEW


(unit : inch)




TOP VIEW




FRONT VIEW




SIDE VIEW

## WARRANTY : 5 Year Parts and Labor Warranty
## 7 Year Compressor Warranty

## STANDARD FEATURES

- ***Anti-corrosion coated evaporator***
- ***Self-contained system***
- ***4" dia. swivel casters standard***

## OPTIONAL ACCESSORIES

- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, ½" - 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600

Ver.20251125

NATURAL Refrigerant · Intertek · Intertek · 5 YEAR WARRANTY · Compressor 7 YEAR WARRANTY (U.S.A only)


- **Turbo Air**: 800-627-0032
- **Bake Tech Innovation**: 800-500-3519
- **Warranty**: 800-381-7770
- **AC**: 888-900-1002



Turbo air (Refrigerator Manufacturer) · BTI Bake Tech Innovation · Turbo air (Refrigeration System) · Texaking

Continued product development may necessitate specification changes without notice.